



VERO MOBILE+

| SYSTEM DIMENSIONS* | FILLING & REFRIGERATION SYSTEM |
|--------------------------------------|--------------------------------|
| HEIGHT | 57.1 in 1450.34 mm |
| WIDTH | 19.9 in 505.46 mm |
| DEPTH | 20.5 in 520.7mm |
| DRY WEIGHT (with Filter pack) | 136 lbs. |

**Requires 4 additional inches of clearance on the back of the machine for proper ventilation and maintenance access.*

CONFIGURATION OF SYSTEM: ALL-IN-ONE MOBILE UNIT: CHILLING & DISPENSING SYSTEM & VERO+ FILTRATION PACK

| | |
|---|--|
| CHILLING CAPACITY | 151 Liters in an hour (varies with ambient water temperature) |
| MAXIMUM FLOW CAPACITY | 240 Liters Per hour |
| POWER VOLTAGE FREQUENCY RUNNING AMPS | 220 V 60 Hz 9 Amps |
| WATER SUPPLY PRESSURE PSI (BAR) | 3/8" Water Line 55 psi min – 60 psi max (2.75 – 4.1 bar) Pre-regulated with proper backflow prevention. |

STANDARD FEATURES

- COLD STILL & AMBIENT
- VERO+ PURIFICATION
- PUSH BUTTON CONTROL
- UV LIGHT TECHNOLOGY
- VOLUMETRIC FLOW METER
- REAR WHEELS | ADJUSTABLE FRONT FEET



BETTER THAN
BOTTLED WATER

VERO MOBILE+



Anti-bacterial UV lamp operating at the outlet on each tap. As demonstrated by numerous studies, UV rays have a sterilizing effect and prevent bacterial proliferation.

